

TKK

CLEAN PROTECT

MARKING SPRAY - RED



FLUORESCENT MARKING SPRAY

Acrylic spray paint for marking on various surfaces. It has good adhesion to surfaces such as wood, metal, glass, concrete, asphalt and almost all types of plastic.

PROPERTIES

- Excellent coverage and visibility.
- Good wear, weather, and chemical resistance.
- Dries quickly.
- Usage 360°.

FIELD OF APPLICATION

- It is used in construction, forestry, for marking outdoor and indoor areas, for horizontal and vertical marking, for marking car parks, danger zones and for limiting work areas.

USAGE INSTRUCTIONS

- The surface to which you apply the paint must be dry and clean.
- Shake the dose well before use. When you hear the sound of metal balls inside the dose, continue shaking for another minute.
- When applying, you can hold the dispenser in any position 15 to 20 cm from the surface to be painted. For highly absorbent substrates, multiple applications are necessary.
- Make sure that the first coat of paint is dry before the second application.

PACKAGING

Aerosol dose 500 ml

STORAGE

36 months in a dry place at a temperature between +5 °C and +25 °C. Store the doses in an upright position.

HEALTH, SAFETY, HANDLING AND DISPOSAL INFORMATION

Follow normal working hygiene. Use only in well-ventilated areas. Additional safety information, safe handling instructions, information on personal protective equipment, and disposal information can be found in the safety data sheet. Safety data sheet available on request. You can also obtain a copy from your TTK sales representative.

WARNING

The information given is based on our tests and practical experience. However, due to specific conditions and working methods we recommend preliminary tests for each case of use.



TKK d. o. o. · Srpenica 1, 5224 Srpenica, Slovenia
+386 [0] 5 38 41 300 | info@tkk-group.com | www.tkk-group.com