


Declaration of Performance

Unique identification code of the product-type:

	HYDROBLOCKER WRC COATING Reference number: 932743545
---	--

Revision: 01 10/02/2017

In accordance with the applicable harmonized technical specification:
EN 14891:2012

Intended use or uses of the construction product:

Liquid applied water impermeable product DM O1, for internal and external installations on walls and floors beneath ceramic tiles (bonded with C2 adhesive).

System or systems of assessment and verification of constancy of performance of the construction product, as set out in Annex V:

System 3

Name and contact address of the manufacturer as required pursuant to Article 11(5): TKK d.o.o., Srpenica 1, 5224 Srpenica

Initial type testing by system 3 was carried out by notified body: ZAG, NB 1404.
Issued report no. P 795/16-420-1.



TKK d. o. o.
Srpenica 1, 5224 Srpenica, Slovenija
T: +386 (0) 5 3841300
F: +386 (0) 5 3841390, 391
E: info@tkk.si
www.tkk.si

Essential characteristics determined according to harmonized technical specification EN 14891:2012	Performance
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after water contact	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after contact with lime water	$\geq 0,5 \text{ N/mm}^2$
Waterproofing	no penetration
Crack bridging ability under standard conditions (23°C)	$\geq 0,75 \text{ mm}$
Crack bridging ability at low temperature (-5°C)	$\geq 0,75 \text{ mm}$

"The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer."

Signed for and on behalf of the manufacturer by:

Marko Štrukelj
Product manager