

# FIX 41

## UNIVERSAL CONTACT ADHESIVE

A universal contact adhesive based on rubber and synthetic resin for bonding of rubber, leather, cork, felt, wood, plastic.

### PROPERTIES

- Flexible joint.
- Fast drying.
- High adhesive strength.
- Moisture resistant.

### AREA OF USE

- For bonding of rubber, leather, cork, felt, wood, plastic.
- Not suitable for polystyrene, PE, PP and PTFE.

### TECHNICAL DATA

Chemical basis	polychloroprene rubber (neoprene)
Consistency	liquid
Curing	Physical curing and crystallization
Density	0.86 g/ml
Temperature resistance	from -20 °C to +70 °C
Application temperature	from 5 °C to 25 °C
Open time	approx. 10 minutes, depending on temperature, humidity and type of substrate

### INSTRUCTIONS FOR USE

- Surfaces must be clean and free of dust and grease.
- Apply the adhesive uniformly with a notched trowel or brush on both sides of the surfaces that need to be glued.
- Wait approx. 10 minutes and join both parts together.

### PACKAGING

- 50 ml and 120 ml tube in a box
- 750 ml dose

### STORAGE

24 months in a dry place at temperatures from 5 °C to 25 °C.

### HEALTH, SAFETY, HANDLING AND DISPOSAL INFORMATION

Additional safety information, safe handling instructions, information on personal protective equipment, and disposal information can be found in the safety data sheet. Safety data sheet available on request. You can also obtain a copy from your TTK sales representative.



**WARNING**

The information given is based on our tests and practical experience. However, due to specific conditions and working methods we recommend preliminary tests for each case of use.



**TKK d.o.o.**  
Srpenica 1, 5224 Srpenica, Slovenia  
+386 5 38 41 300, tkk.si

Visit us on   
**tkk-fix.com**