

TKK

CLEAN PROTECT

DRILL & CUT OIL



COOLING OIL FOR DRILLING AND CUTTING

High-quality spray cooling oil prevents overheating of metals during drilling and cutting.

PROPERTIES

- Reduces friction and metal wear during drilling and cutting and extends tool life.
- Excellent cooling characteristics.
- Prevents the formation of oil mists during cutting and drilling.
- It does not cause corrosion and does not contain silicones.
- The spray can be used at any angle [360°].

FIELD OF APPLICATION

- Suitable for: drilling, milling, cutting, sawing, filing, threading, turning, punching on most metals.

USAGE INSTRUCTIONS

- Shake the dose well before use.
- Spray tools and materials abundantly from a distance of 20 to 25 cm before starting work.
- It is important that the materials remain well moistened during work.

PACKAGING

Aerosol dose 400 ml

STORAGE

36 months in a dry place at a temperature between +5 °C and +25 °C. Store the doses in an upright position.

HEALTH, SAFETY, HANDLING AND DISPOSAL INFORMATION

Follow normal working hygiene. Use only in well-ventilated areas. Additional safety information, safe handling instructions, information on personal protective equipment, and disposal information can be found in the safety data sheet. Safety data sheet available on request. You can also obtain a copy from your TKK sales representative.

WARNING

The information given is based on our tests and practical experience. However, due to specific conditions and working methods we recommend preliminary tests for each case of use.



TKK d. o. o. · Srpenica 1, 5224 Srpenica, Slovenia
+386 [0] 5 38 41 300 | info@tkk-group.com | www.tkk-group.com