

## MULTIPURPOSE SILICONE SPRAY



### MULTI-PURPOSE SILICONE WATER REPELLENT SPRAY

The silicone transparent spray is based on high-performance silicone oil. It creates a water-repellent layer and is useful as a lubricant and release agent in the treatment and processing of plastics, rubber, metals...

### PROPERTIES

- Lubricates and reduces friction and wear.
- Rust-proof.
- Water repellent.
- High temperature resistance.
- For internal and external use
- Can be used at any angle (360°)
- The treated surfaces cannot be painted.
- Not applicable to brake drums and disc brakes.
- Gives plastics and rubber a glossy look.

### FIELD OF APPLICATION

- It is suitable for use on mechanical parts to reduce friction and wear. It can be used for lubricating metals, plastics, and rubber.
- It prevents the build-up of dirt and grease deposits and is therefore suitable for rails.
- Creates a water-repellent layer and protects the electrical wiring of cars, engines, lawnmowers, etc. from moisture.

### USAGE INSTRUCTIONS

- Shake the dose well before use to ensure homogeneity of the contents.
- Spray the silicone spray evenly in a thin layer from a distance of 30-50 cm.
- The optimum separation effect is achieved with a short film application time.
- Thicker application reduces the separating effect.
- Clean and degrease surfaces before first use.
- A single application of silicone spray is sufficient for multiple delamination and lubrication.

### PACKAGING

Aerosol dose 400 ml

**STORAGE**

36 months in a dry place at a temperature between +5 °C and +25 °C. Store the doses in an upright position.

**HEALTH, SAFETY, HANDLING AND DISPOSAL INFORMATION**

Follow normal working hygiene. Use only in well-ventilated areas. Additional safety information, safe handling instructions, information on personal protective equipment, and disposal information can be found in the safety data sheet. Safety data sheet available on request. You can also obtain a copy from your TKK sales representative.

**WARNING**

The information given is based on our tests and practical experience. However, due to specific conditions and working methods we recommend preliminary tests for each case of use.



TKK d. o. o. · Srpenica 1, 5224 Srpenica, Slovenia  
+386 [0] 5 38 41 300 | [info@tkk-group.com](mailto:info@tkk-group.com) | [www.tkk-group.com](http://www.tkk-group.com)