



PLASTIC SELF-ADHESIVE TAPE USED EITHER AS A SEALING OR SPACING MATERIAL. IT IS SUITABLE FOR HOME AND INDUSTRIAL APPLICATIONS AND CONSTRUCTION INDUSTRY.

PROPERTIES

- Easy to handle and use.
- It can be used on all clean and dry surfaces of various materials.
- It does not contain solvents or other corrosive substances.
- It can be painted with usual varnishes on the basis of synthetic resin or oil.

USE

- It can be used either as a sealing or spacing material.
- In roofing industry for sealing seams/joints between metal sheet panels, metal sheet rims and gutters.
- In metal sheet processing industry for sealing overlaps in iron, sheet metal, aluminium, glass and plastic constructions.
- In construction industry as spacers, for sealing overlap joints, window sills, stair steps and façades made of artificial stone.
- It provides corrosion protection between iron and non-ferrous metals.
- In the manufacture of automobiles, railway carriages and caravans for sealing metal, wood and plastic parts.
- It can be used as a lining under ceramic washbasins and toilet bowls.
- It can also be used as a lining under glass-ceramic hobs.

TECHNICAL DATA

Base	synthetic rubber
Appearance	soft rubber
Colour	white
Specific gravity	approx. 2000 kg/m ³
Temperature resistance	between -25 °C and +75 °C

Short instances of high temperature occurring during the process of varnishing [for example 30 minutes at 100 °C] do not cause damage. For individual cases we recommend prior testing.

APPLICATION

- Surfaces on which sealing tapes are used should be clean, dry, dust, rust, fat and oil free.
- Kneading or other preparations are not necessary.

PACKAGING

- 20 mm x 2 mm x 18 m reel.
- 20 mm x 2 mm x 3 m reel.

STORAGE

5 years in a dry space at room temperature.

HEALTH, SAFETY HANDLING AND DISPOSAL INFORMATION

Additional information on safety, safe handling instructions and personal protective equipment as well as disposal information are available in a safety data sheet. Safety data sheet is available upon request. You can also ask your TKK distributor for a copy.

WARNING

Instructions contained in this document are based on our research and experience, however, due to specific conditions and working methods we recommend that you perform preliminary tests prior to any application of our products.



TKK d. o. o. · Srpenica 1, 5224 Srpenica, Slovenija
+386 [0] 5 38 41 300 | info@tkk-group.com | www.tkk-group.com