

ROOF REPAIR SEALANT



TRANSPARENT, ELASTIC SEALANT USED FOR SEALING DRY, WET AND GREASY SURFACES SUCH AS ROOF EDGE TRIMS, CRACKS IN ROOFING EVEN IF MADE OF BITUMEN), JOINTS AROUND CHIMNEYS AS WELL AS TRIMS AROUND ROOF ELEMENTS, SKYLIGHTS, ETC.

PROPERTIES

- Wide range of applications; fast repairs in all weather conditions.
- Suitable for dry as well as greasy surfaces.
- Smooth surfaces may be wet, however, porous ones must be dry.
- Good adhesion on any type of material (asphalt and bitumen included).
- Elastic.
- UV resistance.
- Mould resistance.
- Compatible with copper.
- Easy application.
- It can be painted as soon as after 24 hours.
- Silicone and isocyanate free.
- No primer needed.
- Colour: transparent.

USE

- Crack filling.
- Sealing.
- Sealing of bituminous end joint.
- Sealing of roof capping.
- Repairing various leakages.
- Sealing of various elements on flat roofs.

TECHNICAL DATA

Fresh sealant

Chemical base
Appearance
Curing mechanism
Specific gravity
Skin formation time
Hardening
Application temperature

23/50 % rel. humid.

synthetic rubber with solvents
paste
solvent evaporation
940 ± 10 kg/m³
≈ 15 min.
2 mm/day
between +5 °C and +40 °C

Cured sealant

Hardness Shore A

25 ± 5

Temperature resistance

between -25 °C and +100 °C

APPLICATION

- The surface must be clean and free of loose parts.
- Cut the cartridge at the top and screw on the nozzle, which has to be cut according to the width of the joint and placed in the gun. During work interruption release the handle on the gun and pull the piston back.
- Apply the sealant as evenly as possible.
- At the end, use a smoothing tool - a TTK smoothing instrument, or a TTK SEAL smoothing agent soaped finger to level the sealant.
- If the sealant is used in water, it can become yellow, but this does not affect the quality of the material.
- You may clean the tool used while applying the sealant with TTK CLEAN PROTECT tool cleaner.

PACKAGING

- 300 ml cartridge.

STORAGE

18 months in a dry and cold place under 25 °C in originally closed packaging.

HEALTH, SAFETY HANDLING AND DISPOSAL INFORMATION

Additional information on safety, safe handling instructions and personal protective equipment as well as disposal information are available in a safety data sheet. Safety data sheet is available upon request. You can also ask your TTK distributor for a copy.

WARNING

Instructions contained in this document are based on our research and experience, however, due to specific conditions and working methods we recommend that you perform preliminary tests prior to any application of our products.



TKK d. o. o. · Srpenica 1, 5224 Srpenica, Slovenija
+386 (0) 5 38 41 300 | info@tkk-group.com | www.tkk-group.com