

UNIVERSAL WHITE GREASE



UNIVERSAL WHITE GREASE FOR THE PROTECTION OF MECHANICAL PARTS

White spray grease effectively prevents friction between loaded machine parts.

PROPERTIES

- The grease is waterproof.
- Protects against rust.
- Protects against wear of loaded parts.
- High resistance to salty, acidic, alkaline solutions and atmospheric influences.
- Long-lasting lubricating property even in extreme conditions.
- Ideal for lubricating hard-to-reach parts.

FIELD OF APPLICATION

- It is suitable for lubricating loaded mechanical parts such as ball bearings, axles, gears, conveyor belts, rubber seals.

USAGE INSTRUCTIONS

- Shake the dose well before use.
- When you hear the sound of metal balls inside the dose, continue shaking for another minute.
- Apply the grease on a clean and dry surface.
- Hold the dose 15 to 20 cm from the surface to which the grease is applied. If possible, move the moving parts during application for better coverage.

PACKAGING

Aerosol dose 400 ml

STORAGE

36 months in a dry place at a temperature between +5 °C and +25 °C. Store the doses in an upright position.

HEALTH, SAFETY, HANDLING AND DISPOSAL INFORMATION

Follow normal working hygiene. Use only in well-ventilated areas. Additional safety information, safe handling instructions, information on personal protective equipment, and disposal information can be found in the safety data sheet. Safety data sheet available on request. You can also obtain a copy from your TTK sales representative.

WARNING

The information given is based on our tests and practical experience. However, due to specific conditions and working methods we recommend preliminary tests for each case of use.



TKK d. o. o. · Srpenica 1, 5224 Srpenica, Slovenia
+386 [0] 5 38 41 300 | info@tkk-group.com | www.tkk-group.com