

TKK CLEAN PROTECT WELDING SPRAY



WELDING SPRAY

Welding spray is excellent for cleaning and protection in the welding process. It protects tools and welding elements from sticking of the welding splitters. It does not have any effects on mere welding or on any subsequent varnishing, galvanizing, or chromium-plating.

PROPERTIES

- Long-lasting anti-adhesion effect.
- Makes it easy to clean and change nozzles.
- Not flammable.
- It does not cause corrosion and does not contain silicones.

FIELD OF APPLICATION

- Protects welding tables, welding tools, welding surfaces, other working surfaces from splashing droplets during the welding process.
- Protective coating prevents adhesion and allows easy removal of droplets

USAGE INSTRUCTIONS

- One or two coats are required to protect welded components.
- Spray on the welding nozzles from a distance of 15 cm. To protect the working surface, hold the can at a distance of 30 cm and spray the surface 10 cm to the left and right of the spot weld.
- Allow a few minutes for the solvent to evaporate before you start welding.

PACKAGING

Aerosol dose 400 ml

STORAGE

36 months in a dry place at a temperature between +5 °C and +25 °C. Store the doses in an upright position.

HEALTH, SAFETY, HANDLING AND DISPOSAL INFORMATION

Follow normal working hygiene. Use only in well-ventilated areas. Additional safety information, safe handling instructions, information on personal protective equipment, and disposal information can be found in the safety data sheet. Safety data sheet available on request. You can also obtain a copy from your TKK sales representative.

WARNING

The information given is based on our tests and practical experience. However, due to specific conditions and working methods we recommend preliminary tests for each case of use.



TKK d. o. o. · Srpenica 1, 5224 Srpenica, Slovenia
+386 [0] 5 38 41 300 | info@tkk-group.com | www.tkk-group.com