

DECLARATION OF PERFORMANCE

No: 8030311663

1. Unique identification code of the product-type:

	TKK SEAL UNIVERSAL SILICONE No: 8030311663
---	--

Revision: 02 09/08/2024_GB

In Accordance with the CPR, Regulation [EU] N°305/2011

2. Intended use/es:

- Sealant for façade for interior and exterior application.
- Sealant for sanitary joints

3. Manufacturer:

Name and contact address of the manufacturer as required pursuant to Article 11[5]:
TKK d.o.o., Srpenica 1, 5224 Srpenica

4. Authorised representative:

/

5. System/s of AVCP:

- System 3
- System 3: for reaction to fire

6. Harmonised standard:

- EN 15651-1:2012 : Type F-EXT-INT; 12,5E
- EN 15651-3:2012 : Type S; XS1

Notified body/ies:

ZAG, NB 1404 has carried out Determination of Product Type under system 3.

7. Essential characteristics:	Performance	Harmonised technical specification
TYPE F: EXT-INT		
Reaction to fire	Class F	EN 15651-1
Release of chemicals dangerous to the environment	NPD	
Resistance to flow	≤ 3 mm	
Loss of Volume	≤ 30 %	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elastic recovery	≥ 40%	
Tensile properties at maintained extension	NF	
Adhesion/cohesion at variable temperatures	NF	
Durability	Pass	
TYPE S		
Reaction to fire	Class E	EN 15651-3
Release of chemicals dangerous to the environment	NPD	
Resistance to flow	≤ 5 mm	
Loss of Volume	≤ 55 %	
Adhesion/cohesion after water immersion	NF	
Microbiological growth	0	
Durability	Pass	

Conditioning: method A

Substrate: mortar

"The performance of this product is in conformity with the declared performance.
This declaration of performance is issued under the sole responsibility of the
manufacturer."

Signed for and on behalf of the manufacturer by:

Marko Štrukelj
Head of Product management

 TKK d. o. o.
Srpenica 1
5224 Srpenica
Slovenija

Srpenica, 09/08/2024