

DECLARATION OF PERFORMANCE

No: 949278027

1. Unique identification code of the product-type:

	TKK SEAL FAST DRY ACRYL No: 949278027
---	---

Revision: 02 09/08/2024_GB

In Accordance with the CPR, Regulation [EU] N°305/2011

2. Intended use/es:

- Sealant for façade for interior application.

3. Manufacturer:

Name and contact address of the manufacturer as required pursuant to Article 11[5]:
TKK d.o.o., Srpenica 1, 5224 Srpenica

4. Authorised representative:

/

5. System/s of AVCP:

- System 4
- System 3: for reaction to fire

6. Harmonised standard:

- EN 15651-1:2012 : Type F-INT

Notified body/ies:

ZAG, NB 1404 has carried out Determination of Product Type under system 3.

7. Essential characteristics:	Performance	Harmonised technical specification
TYPE F: INT		EN 15651-1
Reaction to fire	Class E	
Release of chemicals dangerous to the environment	NPD	
Resistance to flow	≤ 5 mm	
Loss of Volume	≤ 45 %	
Elongation at break at [23°]	≥ 25 %	
Durability	Pass	

Conditioning: method A

Substrate: mortar

"The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer."

Signed for and on behalf of the manufacturer by:

Marko Štrukelj
Head of Product management



TKK d. o. o.
Srpenica 1
5224 Srpenica
Slovenija

Srpenica, 09/08/2024