



WATERPROOF COATING

HydroBlocker Waterproof Coating is a fibre-reinforced coating for remedying leakage, filling in cracks and a protective product. It is suitable for use in all weather conditions.

PROPERTIES

- Quick repair in all weather conditions, even when there is rain or snow
 - Suitable for dry and wet surfaces
 - Good adhesion to practically all surfaces – aluminium, zinc, lead, glass, stone, asphalt, bitumen, solid PVC, roof tiles, wood...
 - Simple use
 - No primer required
 - It may be applied to upright surfaces
 - It fills cracks and holes several millimetres wide
 - High elasticity
 - It may be painted with acrylic varnishes
 - Completely resistant to weather conditions
 - Not resistant to solvents
 - Not suitable for use with EPS and PVC foil
-

AREA OF APPLICATION

- For repairing various leaks and filling in cracks
 - For sealing the edges around chimneys, metal finishes, roof gutters, concrete cracks
 - Protective product
 - Sealing inside and outside buildings – balconies, terraces, roofs, fences
 - Also suitable for roadside canals
 - For motor vehicles, boats
-

TECHNICAL INFORMATION

Uncured sealant

Base	synthetic resin with solvents, fibre-reinforced
Appearance	grey paste
Curing mechanism	solvent evaporation
Specific weight	1050 ± 10 kg/m ³
Curing time	24-48 h
Application temperature	from -10°C to 40°C

Cured sealant

Elongation at break	500 ± 50%
Temperature resistance	-25°C to +100°C
Consumption	1-2 l/m ²



WATERPROOF COATING

INSTRUCTIONS FOR USE:

Clean the floors and remove loose parts. Apply a thin layer of the coating with a brush to the cracks at a righangle. In extreme cases, after several days a second layer may be applied.

If the coating is very pasty, it can be diluted to 10% with Tekafin cleaner or nitro thinner or a hydrocarbon-based cleaner (petrol), in order to spread it over the surface easier.

Clean the tools with Tekafin cleaner.

PACKAGING

• 1 l dose

STORAGE

12 months in a dry space at a temperature below 30°C and in originally sealed packaging.

HEALTH, SAFETY, HANDLING AND DISPOSAL INFORMATION

Additional information on safety, instructions for safe treatment, personal protection equipment, as well as disposal information, are located in the safety data sheet. The safety data sheet may be received upon request. You may also receive a copy from your TKK sales representative.

WARNING

Instructions were given based on our research and experiences, however, due to special requests, specific conditions and manners of work, we recommend that testing be done for each case of use.
